



**NOTES**

- DESIGN PRESSURE 4.5MPA
- THE MINIMUM BURST PRESSURE OF THE PRODUCT IS THREE TIMES THE DESIGN PRESSURE
- DIAGONAL DIFFERENCE MAX 5mm
- TOLERANCE IF NOT SPECIFIED SHALL COMPLY WITH STANDARD ISO 2768-1 CLASS C (GB/T 1804 CLASS C)
- SEAL 0.01~0.05MPA NITROGEN GAS IN THE PRODUCT
- OTHER STANDARDS JB/T11967 EN378- 2
- THE INLET AND OUTLET PIPES ARE COPPER PIPES

**PRODUCT PARAMETERS**

TUBE NUMBER	52
TUBE TYPE	16*1.3- 16
TUBE MATERIAL	LLA9153(3F03)+Zn- H112
(LONG USING LIFE ALLOY)	
MANIFOLD TYPE	φ20
FIN TYPE	LOUVERED 16*0.08 FPI 23
FIN MATERIAL	AA4343/3003/4343
PASS	28/24



UNMARKED TOLERANCE	DESCRIPTION: Microchannel heat exchanger	
	MODEL: RC-1300-S	REV. A
VIEW	CODE: 021U0083R	CREAT:
		AUDIT:
APPROVED BY CUSTOMER SIGNATURE:		PROCESS: APPROVE:

X ±1.5  
X.X ±1  
X.XX ±0.5  
/ ±1°

