



NOTES

- 1 DESIGN PRESSURE 4.5MPA
- 2 THE MINIMUM BURST PRESSURE OF THE PRODUCT IS THREE TIMES THE DESIGN PRESSURE
- 3 DIAGONAL DIFFERENCE MAX 11mm
- 4 TOLERANCE IF NOT SPECIFIED SHALL COMPLY WITH STANDARD ISO 2768-1 CLASS C(GB/T 1804 CLASS C)
- 5 SEAL 0.01~0.05MPA NITROGEN GAS IN THE PRODUCT
- 6 OTHER STANDARDS JB/T11967 EN378-2
- 7 THE INLET AND OUTLET PIPES ARE COPPER PIPES

PRODUCT PARAMETERS

TUBE NUMBER 103
 TUBE TYPE 25.4*2- 20
 TUBE MATERIAL LLA9153(3F03)+Zn- H112
 (LONG USING LIFE ALLOY)
 MANIFOLD TYPE ϕ38
 FIN TYPE LOUVERED 25.4*0.08 FPI 23
 FIN MATERIAL AA4343/3003/4343
 PASS 69/34



UNMARKED TOLERANCE X ±1.5 X.X ±1 X.XX ±0.5 ∠ ±1°	DESCRIPTION: Microchannel heat exchanger	
	MODEL: RC-2000-I	REV. A
VIEW ⊕ □	CODE: 021U0265R	CREAT: AUDIT:
APPROVED BY CUSTOMER SIGNATURE:	PROCESS: APPROVE:	