



- NOTES**
- DESIGN PRESSURE 4.5MPA
  - THE MINIMUM BURST PRESSURE OF THE PRODUCT IS THREE TIMES THE DESIGN PRESSURE
  - DIAGONAL DIFFERENCE MAX 5mm
  - TOLERANCE IF NOT SPECIFIED SHALL COMPLY WITH STANDARD ISO 2768-1 CLASS C (GB/T 1804 CLASS C)
  - SEAL 0.01~0.05MPA NITROGEN GAS IN THE PRODUCT
  - OTHER STANDARDS JB/T11967 EN378- 2
  - THE INLET AND OUTLET PIPES ARE COPPER PIPES

PRODUCT PARAMETERS	
TUBE NUMBER	52
TUBE TYPE	16*1.3- 16
TUBE MATERIAL	LLA9153(3F03)+Zn- H112
(LONG USING LIFE ALLOY)	
MANIFOLD TYPE	φ20
FIN TYPE	LOUVERED 16*0.08 FPI 23
FIN MATERIAL	AA4343/3003/4343
PASS	28/24



UNMARKED TOLERANCE	DESCRIPTION:	
	Microchannel heat exchanger	
X ±1.5 X.X ±1 X.XX ±0.5 / ±1°	MODEL:	REV.
	RC-1300-I	A
VIEW	CODE:	CREAT:
	021U0090R	AUDIT:
APPROVED BY CUSTOMER SIGNATURE:	PROCESS:	
	APPROVE:	